

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



1/22

100

OPTICAL
AMPLIFIER




FIG. 1



2/22

200




FIG. 2



3/22

FIG. 3A




FIG. 3B





FIG. 3C





4/22




FIG. 4



5/22

500




FIG. 5



6/22




FIG. 6A

7/22




FIG. 6B



8/22

700




FIG. 7



9/22

800




FIG. 8



10/22




FIG. 9A




FIG. 9B




FIG. 9C



11/22




FIG. 10

12/22




FIG. 11



13/22

1200




FIG. 12



14/22




FIG. 13



15/22




FIG. 14A




FIG. 14B

1430

P_{in} (dBm)	G_1 (dB)	G_2 (dB)	P_{out} (dBm)
-11	0	30	9.18
-11	5	25	9.17
-11	10	20	9.16
-11	15	15	9.10

FIG. 14C



1500

CIRCULATOR

OPTICAL AMPLIFIER

CIRCULATOR




FIG. 15



17/22




FIG. 16



18/22




FIG. 17





FIG. 18A



Assumptions :
 -10dB input SNR
 (5 GHz bandwidth)
 -5 dB amplifier NF

Results :
 16 dB improvement in SNR

FIG. 18B




FIG. 18C

20/22



1900




FIG. 19



2000




FIG. 20

22/22



2100




FIG. 21